

Technical Data / Equipment

	Cortex CB 495/5K SLICER	Cortex CB 495/7K SLICER	Cortex CB 435/4E COMPACT SLICER
Diameter of blades (mm)	200 / 300	200 / 300	200
Maximum processing height (mm)	70 / 120	70 / 120	70
Cutting width (processing width) (mm)	400	600	300
Available steps of blade distances (mm)	6 - 7 - 8 - 9 - 10 - 11 ①	6 - 7 - 8 - 9 - 10 - 11 ①	6 - 7 - 8 - 9 - 10 - 11 ①
Infeed conveyor belt	●	●	●
Output conveyor belt	●	●	○
Cutting speed (m/min)	18 ②	18 ②	18 ②
Adjustable lateral guides at infeed conveyor belt	○	○	○
Motor performance (kW)	1.5	1.5	1.1
Electrical connection	3 AC - 400 / 230 Volt - 50 (60) Hz ③		
Dimensions W x H x D (mm)	820 x 1300 x 2450	1020 x 1300 x 2450	700 x 1190 x 1250 ④
Weight (kg)	260 ⑤	320 ⑤	200 ⑤
Lift-out-device for blade shaft	●	●	●
Safety cover for blades	●	●	●
Transport roller can be adjusted when diameter is decreasing	●	●	-
Cleaning wagon for 2 blade shafts	○	○	○
NOCK POWER PLATES®	●	●	●
NOCK EASY FLOW® safety cover	●	●	●
Lockable castor rollers	●	●	●
Stainless steel	●	●	●
Compressed air consumption	-	-	-

- ① different blade distances in one machine possible
- ② other cutting speeds upon request
- ③ other voltages upon request
- ④ without output belt
- ⑤ with blade gap 8 mm and diameter of blades 200 mm

● **standard**

○ **optional**

NOCK Fleischereimaschinen GmbH
Industriestraße 14
D-77948 Friesenheim
GERMANY

Telefon +49 (0) 7821-99 78 16
Telefax +49 (0) 7821-99 78 18
E-Mail: info@nock-gmbh.com
www.nock-gmbh.com