

Features + equipment / Derinding machines

model	pressure roller		open top (manual) operation possible	output conveyor belt	discharge conveyor belt for removed skin	infeed table for manual operation	plastic modular belts	spring- suspended blade holder mounting	tooth roller with scraper comb	NOCK POWER PLATES®	NOCK EASY-FLOW® safety cover	lockable castors	stainless steel ②	particulary suitable for	
	spring- suspended	adjustable in height												small trade	industry
Cortex CB 430	●		●	○		●	○	●	●	●	●	●	●	●	●
Cortex CB 496	●	●	●	○	○	●	○	●	●	●	●	●	●	●	●
Cortex CB 503	●	●		●	○		○	●	●	●	●	●	●		●
Cortex CB 504	●	●		●	○		○	●	●	●	●	● ^①	●		●
Cortex CB 604	●	●		●	○		○	●	●	●	●	● ^①	●		●
Cortex CB 704	●	●		●	○		○	●	●	●	●	● ^①	●		●
Cortex CB 501 SERRANO	●	●		●	○		○	●	●	●	●	●	●		●
Cortex C 420			●						●				●	●	
Cortex C 460			●					●	●	●		●	●	●	●
Cortex C 560			●					●	●	●		●	●	●	●

- standard
- optional

Further options:

- Inflated pressure ballon (soft ballon)
- NOCK Integrated Product Return System®
- Pneumatic quick-adjustment of blade holder (CB 501)
- Transfer plate for passing without derinding

① alternative: without underframe for integration in cutting lines

② including all ball bearings