

## Technical data + equipment / Membrane skinning machines Vliesex

|  | Vliesex V 460N   | Vliesex V 560N  | Vliesex V 4744 TURBO | Vliesex V 5744 TURBO |
|--|--|-----------------|----------------------|----------------------|
| cutting width (mm)   | 430  | 500             | 430                  | 500                  |
| cutting speed (m/min)  | 37   | 37              | 44                   | 44                   |
| transport roller without grooves                               | ●  | ●               | ●                    | ●                    |
| dynamic (counter rotating) stainless steel cleaning roller     | ●  | ●               | ●                    | ●                    |
| NOCK Air Jet compressed air cleaning system                    | ●  | ●               | ●                    | ●                    |
| foot switch adjustable in height                               | ●  | ●               | ●                    | ●                    |
| spring suspended blade holder                                  | ●  | ●               | ●                    | ●                    |
| quick change system for blades                                 | –  | –               | ○                    | ○                    |
| automatic adjustment of blade holder when starting the machine | –  | –               | ●                    | ●                    |
| barrier free processing table                                  | –  | –               | ●                    | ●                    |
| lockable castors   | ●  | ●               | ●                    | ●                    |
| NOCK POWER PLATES®   | ●  | ●               | ●                    | ●                    |
| compressed air connection (bar)                                | 5 < p < 10 – quick lock coupling DN 7.2 (G <sup>1</sup> / <sub>4</sub> “ external) |                 |                      |                      |
| compressed air consumption                                     | approx. 250 l/min (ambient pressure)   |                 |                      |                      |
| adjustable pressure reducer                                    | ●  | ●               | ●                    | ●                    |
| motor performance (kW)   | 0.75   | 0.75            | 1.1                  | 1.1                  |
| electrical connection  | 3 AC - 400/230 Volt - 50 (60) Hz <sup>①</sup>                                      |                 |                      |                      |
| weight (kg)  | 150  | 180             | 170                  | 200                  |
| overall dimension W x H x D (mm)                               | 740 x 960 x 630  | 800 x 960 x 630 | 740 x 930 x 630      | 800 x 930 x 630      |
| stainless steel  | ●  | ●               | ●                    | ●                    |
| blade dimension (mm)   | 460 x 20 x 1   | 520 x 20 x 1    | 460 x 20 x 1         | 520 x 20 x 1         |

① other voltages upon request

● standard

○ optional

NOCK Maschinenbau GmbH  
 Industriestrasse 14  
 77948 Friesenheim  
 GERMANY

Tel: +49 (0) 7821-99 78 16  
 Fax: +49 (0) 7821-99 78 18  
 E-mail: info@nock-gmbh.com  
 www.nock-gmbh.com