



Know-how in food processing!

NOCK combination machine Cortex CBV 460

Application range

Automatic derinding of flat and high pieces.
Derinding of large round pieces in open top (manual) operation.
Membrane skinning / skinning of pork, beef, veal, lamb, game, turkey and poultry with open top operation.

Standard equipment

- transport roller without circumferential grooves = blade roller
- two-speed motor
- dynamic stainless steel cleaning roller and **NOCK Air-Jet compressed air cleaning system** keep the transport roller constantly clean during operation
- blade gap infinitely adjustable
- blade holder suspension spring loaded for perfect skinning results
- spring suspended pressure roller, **3-stage variability in height**
- **infeed conveyor and pressure roller** for automatic derinding, can be removed without tools
- **exchangeable infeed table and foot switch bar** to skin with open top (machine can be effortlessly converted)
- discharge slide sheet
- **safety cover**
- **access protection at the rear** for more safety at work
- **NOCK POWER PLATES®** provide robustness and service friendliness
- **centring plate** positions the stacking container (E1, E2), can be removed without tools



Cortex CBV 460



Cortex CBV 460, rear view with optional discharge conveyor

Options

- discharge conveyor with safety cover for increased safety at work
- plastic modular belts
- inflated pressure balloon
- cleaning trolley / storage trolley

Further advantages

- low side walls for optimal working in manual derinding
- Made in Germany



Cortex CBV 460, open top

Technical Data Cortex CBV 460

cutting width :	430 mm	NOCK Maschinenbau GmbH Industriestraße 14 77948 Friesenheim GERMANY Phone: +49 (0) 7821 / 923898-0 Fax: +49 (0) 7821 / 923898-18 E-mail: info@nock-gmbh.com Internet: www.nock-gmbh.com
cutting speed :	17 m/min (derinding) 31 m/min (membrane skinning)	
max. throughput height :	90 mm	
motor performance :	0,55 / 0,88 kW	
electrical connection :	3 L - PE - 400 V - 50 Hz ¹⁾	
weight :	218 / 230 kg ²⁾	
overall dimension W x H x D :	800 x 2025 x 1250 / 1820 mm ²⁾	

- 1) other voltages upon request
2) without/with discharge conveyor

Subject to technical changes

issued: 04/2023