

## Technical data + equipment / Skinex SBW 496 WHITE FISH

cutting width	430 mm
infeed conveyor speed	28 m/min
blade gap (stepless)	0 - 3 mm
max. throughput height	70 mm
skinning technology	S technology with transport roller without peripheral grooves, with dynamic cleaning roller
NOCK ACTIVE SKIN GRIPPER® ASG	●
pressure unit	NOCK MULTI-DISC® upper pressure belt
skinning by pulling off with blunt blade (silver skinning)	●
skinning with a sharp blade	● ①
infeed conveyor	●
discharge conveyor	●
discharge conveyor for removed skin	○
apply length on the infeed conveyor	400 mm
overall dimension W x H x D	750 x 1220 x 1820 mm
weight	260 kg
motor performance	1.1 kW
electric connection	3 AC - 400 V - 50 Hz ② IEC 60309 16 A 6h
compressed air connection	5 < p < 10 bar
compressed air consumption	approx. 50 l/min (ambient pressure)
water connection	G 1/2 internal thread
water consumption	approx. 200 l/h
NOCK POWER PLATES®	●
NOCK EASY FLOW® safety cover	●
lockable castors	●
stainless steel	●
transport roller made of AISI 316L stainless steel	●
stainless steel bearings	●

● standard

○ optional

① with activated NOCK ACTIVE SKIN GRIPPER® ASG

② other voltages upon request



NOCK Maschinenbau GmbH  
Industriestrasse 14  
77948 Friesenheim  
GERMANY

Tel.: +49 (0) 7821-92 38 98-0  
Fax: +49 (0) 7821-92 38 98-18  
E-mail: [info@nock-gmbh.com](mailto:info@nock-gmbh.com)  
[www.nock-gmbh.com](http://www.nock-gmbh.com)